

SC-324-XB



FEATURES

4MP True WDR EXIR Bullet Camera

- 4 Megapixel High Resolution
- Full HD 4MP Video Output
- Low Illumination
- 3D DNR; True WDR; BLC
- IP67 Rating
- IR Range: up to 150ft
- True Day / Night
- H.265

Specifications

Model Number	SC-324-XB
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F2.0 (2.8mm optional) Angle of view: 78.7°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Max. Image Resolution	2688 x 1520
Frame rate	30fps (2688 x 1520)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Specifications	
Network storage	NAS
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 9.5W
Weather proof rating	IP67
IR range	UP to 150ft
Dimension	Φ4.13" × 11.8"
Weight	2.65lbs
Electrical Box	HTH-260ZJ